



Safety

SAFETY

Head and Eye Protection | Hard Hats and Spectacles



(A)

MSA V-Gard® Elite Cap

- Provides greater visibility and extra protection from sun and rain
- Significantly reduces glare, helping to reduce eye strain caused by reflected light
- "Wear and Fit" Straz-on suspension allows for quick and simple adjustments while wearing the cap

Code	Description	UOM/Qty	Image
MS226000WH	V-Gard Elite Cap White	Ea/1	(A)
MS226000YE	V-Gard Elite Cap Yellow	Ea/1	

Other colours available, please contact your Bunzl Representative for more information.



(B)

Crews Yukon Visitor Eyewear

- Medium impact poly carbonate wraparound scratch-resistant lens
- Ventilated temples to reduce fogging
- Provides excellent peripheral vision
- Moulded in brow guard and vented side shields
- Approved to Australian Standard AS/NZS1337

Code	Frame	Lens	UOM/Qty	Image
CRAS9800	Clear	Clear	Pr/1	(B)



(C)

Crews Bearkat

- Vision is unobstructed by the one-piece wraparound scratch resistance lens
- Comfort is enhanced by the flexible temples and the nonslip rubber head grips
- Poly carbonate lens provide UV protection

Code	Temple Style	Lens	UOM/Qty	Image
CRASBK110AF	Polycarbonate	Clear	Pr/1	(C)
CRASBK112AF	Polycarbonate	Grey	Pr/1	
CRASBK113AF	Polycarbonate	Light Blue	Pr/1	



(E)

Crews Checkmate

- Flexible bayonet temples for a more comfortable fit to a broader cross-section of facial and head sizes
- Light on weight but heavy on protection with medium impact and UV polycarbonate lens
- Features Crews exclusive AF4 Anti fog lens coating
- Approved to Australian Standard AS/NZS1337

Code	Temple Style	Lens	UOM/Qty	Image
CRASCK112AF	Polycarbonate	Grey	Pr/1	(E)
CRASCK210AF	Polycarbonate	Clear	Pr/144	



(F)

Bollé Bandido

- Lightweight one piece rim less frame
- 10 base curved lenses & distortion free
- Anti fog, scratch resistant, 100% UV protection
- Ideal for manufacturing, petrochemicals, construction, mining, medical & dental

Code	Frame	Lens	UOM/Qty	Image
BO1667201	Clear	Clear	Pr/1	(F)
BO1667202	Smoke	Dark Smoke	Pr/1	

Crews Verdict Goggles

- Dust proof medium impact chemical goggle
- Can fit easily over prescription spectacles

Code	Lens	UOM/Qty	Image
CRAS2410	Clear	Pr/1	(A)



3M™ Peltor® Splash GoggleGear™ with Strap

- Lightweight, contoured, low profile design
- A soft PVC shroud gently hugs the face and has indirect venting to allow cooling air flow and help reduce fogging
- Lens protected by AO Safety's exclusive DX™ anti-fog hard coat resists fogging, scratching, static and most chemicals
- AS/NZS 1337:1992

Code	Frame	Lens	UOM/Qty	Image
AE16602	Medium	Clear	Pr/1	(B)



Crews Len's Cleaning Towelette

- Useful for cleaning plastic, polycarbonate or glass lenses and goggles
- Easy to store
- Reduces fogging and static cling

Code	Colour	UOM/Qty	Image
CRLCT	White	Pk/100	(C)



SAFETY

Hearing Protection | Ear Plugs



(A)

3M™ E.A.R® Classic® Ear Plugs

- Highest attenuation levels
- Easy to use all day comfort
- Foam expands to form a comfortable seal
- Nonirritating and moisture-resistant

Code	Description	SLC ₈₀	Class	UOM/Qty	Image
AE312-1201	Uncorded PB	23dB	4	Bx/200	(A)



(B)

3M™ E.A.R® Ultrafit™ Ear Plugs

- Ready to use protection
- Triple flange design, comfortable, universal size
- Nonirritating, washable and reusable

Code	Description	SLC ₈₀	Class	UOM/Qty	Image
AE340-4002	Corded In Carry Case	18dB	3	Bx/50 Pr	(B)
AE340-4004	Corded In Polybag	18dB	3	Bx/100 Pr	



(C)

3M™ E.A.Rsoft™ SuperFit™ Ear Plugs

- Cylindrical design features an improved formula for increased softness all day comfort and a secure fit in a wide range of ear canals
- Provides highest protection level

Code	Description	SLC ₈₀	Class	UOM/Qty	Image
AE311-1254	Regular Corded PB	24dB	4	Bx/200 Pr	(C)
AE312-1256	Regular Uncorded PB	24dB	4	Bx/200 Pr	
AE391-1254	Regular Uncorded Dispenser Refill	24dB	4	Bx/500 Pr	



(D)

3M™ E.A.R® Metal Detectable

- Comfortable
- Hygienic, reusable and metal detectable

Code	Description	SLC ₈₀	Class	UOM/Qty	Image
AE311-4106	Soft Metal Detectable Corded Regular	23dB	4	Bx/200 Pr	(D)
AE340-5007	Ultrafit Metal Detectable Corded Regular	18dB	3	Bx/100 Pr	



(E)



(F)

3M™ Peltor® Next Nitro Ear Plugs

- Ultra-soft foam formulation for comfortable all day wear
- Tapered shape for easy insertion and excellent canal-hugging seal

Code	Description	SLC ₈₀	Class	UOM/Qty	Image
AE311-1254	Uncorded	26dB	5	Bx/200 Pr	(F)
AE311-1256	Corded	27dB	5	Bx/200 Pr	

3M™ Peltor® H6 Series Low Profile Earmuffs

- Slim design, specially engineered for high comfort and continuous wear
- Liquid and foam-filled ear cushion

Code	Description	SLC ₉₀	Class	UOM/Qty	Image
AEH6A	H6 Headband Earmuffs	22dB	4	Pr/1	(A)



3M™ Peltor® H7 Series Deluxe Earmuffs

- Covers both severe and high noise levels
- Meets the protection requirements of most working environments

Code	Description	SLC ₉₀	Class	UOM/Qty	Image
AEH7A	H7 Headband Earmuffs	30dB	5	Pr/1	(B)



3M™ Peltor® H9 Series Select Performance Earmuffs

- Lightweight and comfortable protection

Code	Description	SLC ₉₀	Class	UOM/Qty	Image
AEH9A	H9 Headband Earmuffs	24dB	4	Pr/1	(C)



SAFETY

Respiratory Protection | Respirators



(A)



(B)



(C)



(D)



(E)



(F)



(G)

3M™ Flat Fold Respirators

- Unique 3 panel flat fold design
- P1 for mechanically generated particles eg. grinding, sanding, crushing, sawing
- P2 for mechanically and thermally generated particles and fumes eg. grinding, sanding, crushing, sawing, smoke, welding fume
- 3M Cool Flow™ Exhalation Valve prevents heat and moisture build-up, making breathing easier
- Individually wrapped
- Meets performance requirements of AS/NZ 1716

Code	Description	UOM/Qty	Image
TM9310	P1 Non Valved	Bx/20	(A)
TM9320	P2 Non Valved	Bx/20	(B)
TM9322	P2 Valved	Bx/10	(C)

3M™ Cupped Respirators

- P1 for mechanically generated particles eg. grinding, sanding, crushing, sawing
- P2 for mechanically and thermally generated particles and fumes eg. grinding, sanding, crushing, sawing, smoke, welding fume
- 3M Cool Flow™ Exhalation Valve prevents heat and moisture build-up, making breathing easier
- Meets performance requirements of AS/NZ 1716

Code	Description	UOM/Qty	Image
TM8710	P1 Non Valved	Bx/20	(D)
TM8812	P1 Valved	Bx/10	(E)
TM8210	P2 Non Valved	Bx/20	(F)
TM8822	P2 Valved	Bx/10	(G)